

DuPont™ Zytel® 73G15L NC010

NYLON RESIN

Product Information

Common features of Zytel® nylon resin include mechanical and physical properties such as high mechanical strength, excellent balance of stiffness and toughness, good high temperature performance, good electrical and flammability properties, good abrasion and chemical resistance. In addition, Zytel® nylon resins are available in different modified and reinforced grades to create a wide range of products with tailored properties for specific processes and end-uses. Zytel® nylon resin, including most flame retardant grades, offer the ability to be coloured.

The good melt stability of Zytel® nylon resin normally enables the recycling of properly handled production waste. If recycling is not possible, DuPont recommends, as the preferred option, incineration with energy recovery (-31kJ/g of base polymer) in appropriately equipped installations. For disposal, local regulations have to be observed.

Zytel® nylon resin typically is used in demanding applications in the automotive, furniture, domestic appliances, sporting goods and construction industry.

Zytel® 73G15L NC010 is a 15% glass fiber reinforced polyamide 6 resin for injection molding.

General information	Value	Unit	Test Standard
Resin Identification	PA6-GF15	-	ISO 1043
Part Marking Code	PA6-GF15	-	ISO 11469
Rheological properties	dry / cond	Unit	Test Standard
Molding shrinkage, parallel	0.3 / -	%	ISO 294-4, 2577
Molding shrinkage, normal	0.8 / -	%	ISO 294-4, 2577
Mechanical properties	dry / cond	Unit	Test Standard
Tensile Modulus	870228 / 507633	psi	ISO 527-1/-2
Stress at break	19600 / 10400	psi	ISO 527-1/-2
Strain at break	4 / 10	%	ISO 527-1/-2
Flexural Modulus	725000 / -	psi	ISO 178
Charpy impact strength			ISO 179/1eU
73°F	23.8 / 45.2	ftlb/in ²	
-22°F	21.4 / 25.7	ftlb/in ²	
Charpy notched impact strength			ISO 179/1eA
73°F	3.33 / 7.14	ftlb/in ²	
-22°F	2.85 / 6.66	ftlb/in ²	
-40°F	2.85 / -	ftlb/in ²	
Izod notched impact strength			ISO 180/1A
73°F	2.85 / 5.71	ftlb/in ²	
-22°F	2.38 / -	ftlb/in ²	
-40°F	2.38 / -	ftlb/in ²	
Izod impact strength			ISO 180/1U
73°F	21.4 / -	ftlb/in ²	
-40°F	19 / -	ftlb/in ²	
Thermal properties	dry / cond	Unit	Test Standard
Melting temperature, 18°F/min	430 / *	°F	ISO 11357-1/-3
Temp. of deflection under load			ISO 75-1/-2
260 psi	392 / *	°F	
65 psi	428 / *	°F	
Vicat softening temperature, 90°F/h, 11 lbf	419 / *	°F	ISO 306
Coeff. of linear therm. expansion, parallel	2.06E-5 / *	in/in/°F	ISO 11359-1/-2
Coeff. of linear therm. expansion, normal	6.06E-5 / *	in/in/°F	ISO 11359-1/-2
Thermal conductivity of melt	0.19	W/(m K)	-
Spec. heat capacity of melt	2470	J/(kg K)	-
RTI, electrical, 60mil	149 / *	°F	UL 746B
RTI, impact, 60mil	149 / *	°F	UL 746B
RTI, strength, 60mil	149 / *	°F	UL 746B
Flammability	dry / cond	Unit	Test Standard
Burning Behav. at 60mil nom. thickn.	HB / *	class	IEC 60695-11-10
Thickness tested	0.0591 / *	in	IEC 60695-11-10

To find out more, visit [DuPont Performance Polymers](#) or contact nearest DuPont location.

North America

Tel: +1 302 999-4592

Toll-Free (USA): 800 441-0575

Asia Pacific

Tel: +81 3 5521 8600

Europe/Middle East/Africa

Tel: +41 22 717 51 11



DuPont™ Zytel® 73G15L NC010

NYLON RESIN

UL recognition	yes / *	-	UL 94	
Burning Behav. at thickness h	HB / *	class	IEC 60695-11-10	
Thickness tested	0.0591 / *	in	IEC 60695-11-10	
UL recognition	yes / *	-	UL 94	
Oxygen index	21 / *	%	ISO 4589-1/-2	
FMVSS Class	B	-	ISO 3795 (FMVSS 302)	
Burning rate, Thickness 1 mm	0.984	in/min	ISO 3795 (FMVSS 302)	DS

DS: Derived from similar grade

Other properties	dry / cond	Unit	Test Standard	
Humidity absorption, 80mil	2.5 / *	%	Sim. to ISO 62	
Water absorption, 80mil	7.6 / *	%	Sim. to ISO 62	
Density	1.23 / -	g/cm ³	ISO 1183	
Density of melt	66.8	lb/ft ³	-	

VDA Properties	dry / cond	Unit	Test Standard	
Odor test	4	class	VDA 270	DS
Fogging, G-value (condensate)	0 / *	mg	ISO 6452	

DS: Derived from similar grade

Injection	dry / cond	Unit	Test Standard	
Drying Recommended	yes	-	-	
Drying Temperature	176	°F	-	
Drying Time, Dehumidified Dryer	2 - 4	h	-	
Processing Moisture Content	≤0.2	%	-	
Melt Temperature Optimum	518	°F	-	
Min. melt temperature	500	°F	-	
Max. melt temperature	536	°F	-	
Max. screw tangential speed	0.2 / *	m/s	-	
Mold Temperature Optimum	212	°F	-	
Min. mold temperature	158	°F	-	
Max. mold temperature	248	°F	-	
Hold pressure range	7250 - 14500	psi	-	
Hold pressure time	0.0762	s/mil	-	

Characteristics				
Processing	• Injection Molding			
Delivery form	• Pellets			
Additives	• Lubricants	• Release agent		
Regional Availability	• North America	• Asia Pacific	• Near East/Africa	
	• Europe	• South and Central America	• Global	

To find out more, visit [DuPont Performance Polymers](#) or contact nearest DuPont location.

North America

Tel: +1 302 999-4592

Toll-Free (USA): 800 441-0575

Asia Pacific

Tel: +81 3 5521 8600

Europe/Middle East/Africa

Tel: +41 22 717 51 11




DuPont™ Zytel® 73G15L NC010

NYLON RESIN

Diagrams

Dynamic Shear modulus-temperature (dry)



Revised: 2016-10-03

Page: 3 of 10

To find out more, visit [DuPont Performance Polymers](#) or contact nearest DuPont location.

North America

Tel: +1 302 999-4592

Toll-Free (USA): 800 441-0575

Asia Pacific

Tel: +81 3 5521 8600

Europe/Middle East/Africa

Tel: +41 22 717 51 11


Copyright 2017 DuPont. The DuPont Oval Logo is a trademark or registered trademark of E.I. du Pont de Nemours and Company or its affiliates. All rights reserved.



DuPont™ Zytel® 73G15L NC010

NYLON RESIN

Stress-strain (dry)



To find out more, visit [DuPont Performance Polymers](#) or contact nearest DuPont location.

North America

Tel: +1 302 999-4592

Toll-Free (USA): 800 441-0575

Asia Pacific

Tel: +81 3 5521 8600

Europe/Middle East/Africa


Tel: +41 22 717 51 11



DuPont™ Zytel® 73G15L NC010

NYLON RESIN

Stress-strain (cond.)



全球代理 全球信赖
 服务热线: 18128015760
 或0769-87120762 刘先生

To find out more, visit [DuPont Performance Polymers](#) or contact nearest DuPont location.

North America

Tel: +1 302 999-4592

Toll-Free (USA): 800 441-0575

Asia Pacific

Tel: +81 3 5521 8600

Europe/Middle East/Africa


Tel: +41 22 717 51 11



DuPont™ Zytel® 73G15L NC010

NYLON RESIN

Secant modulus-strain (dry)



To find out more, visit [DuPont Performance Polymers](#) or contact nearest DuPont location.

North America

Tel: +1 302 999-4592

Toll-Free (USA): 800 441-0575

Asia Pacific

Tel: +81 3 5521 8600

Europe/Middle East/Africa


Tel: +41 22 717 51 11



DuPont™ Zytel® 73G15L NC010

NYLON RESIN

Secant modulus-strain (cond.)



To find out more, visit [DuPont Performance Polymers](#) or contact nearest DuPont location.

North America

Tel: +1 302 999-4592

Toll-Free (USA): 800 441-0575

Asia Pacific

Tel: +81 3 5521 8600

Europe/Middle East/Africa


Tel: +41 22 717 51 11




DuPont™ Zytel® 73G15L NC010

NYLON RESIN

Tensile modulus-temperature (dry)



Tensile modulus-temperature (cond.)



To find out more, visit [DuPont Performance Polymers](#) or contact nearest DuPont location.

North America

Tel: +1 302 999-4592

Toll-Free (USA): 800 441-0575

Asia Pacific

Tel: +81 3 5521 8600

Europe/Middle East/Africa

Tel: +41 22 717 51 11



DuPont™ Zytel® 73G15L NC010

NYLON RESIN

Chemical Media Resistance

Acids

- ✓ Acetic Acid (5% by mass) (23°C)
- ✓ Citric Acid solution (10% by mass) (23°C)
- ✓ Lactic Acid (10% by mass) (23°C)
- ✗ Hydrochloric Acid (36% by mass) (23°C)
- ✗ Nitric Acid (40% by mass) (23°C)
- ✗ Sulfuric Acid (38% by mass) (23°C)
- ✗ Sulfuric Acid (5% by mass) (23°C)
- ✗ Chromic Acid solution (40% by mass) (23°C)

Bases

- ✗ Sodium Hydroxide solution (35% by mass) (23°C)
- ✓ Sodium Hydroxide solution (1% by mass) (23°C)
- ✓ Ammonium Hydroxide solution (10% by mass) (23°C)

Alcohols

- ✓ Isopropyl alcohol (23°C)
- ✓ Methanol (23°C)
- ✓ Ethanol (23°C)

Hydrocarbons

- ✓ n-Hexane (23°C)
- ✓ Toluene (23°C)
- ✓ iso-Octane (23°C)

Ketones

- ✓ Acetone (23°C)

Ethers

- ✓ Diethyl ether (23°C)

Mineral oils

- ✓ SAE 10W40 multigrade motor oil (23°C)
- ✓ SAE 10W40 multigrade motor oil (130°C)
- ✓ SAE 80/90 hypoid-gear oil (130°C)
- ✓ Insulating Oil (23°C)

Standard Fuels

- ✓ ISO 1817 Liquid 1 - E5 (60°C)
- ✓ ISO 1817 Liquid 2 - M15E4 (60°C)
- ✗ ISO 1817 Liquid 3 - M3E7 (60°C)
- ✗ ISO 1817 Liquid 4 - M15 (60°C)
- ✓ Standard fuel without alcohol (pref. ISO 1817 Liquid C) (23°C)
- ✓ Standard fuel with alcohol (pref. ISO 1817 Liquid 4) (23°C)



DuPont™ Zytel® 73G15L NC010

NYLON RESIN

- ✓ Diesel fuel (pref. ISO 1817 Liquid F) (23°C)
- ✗ Diesel fuel (pref. ISO 1817 Liquid F) (90°C)
- ✗ Diesel fuel (pref. ISO 1817 Liquid F) (>90°C)

Salt solutions

- ✓ Sodium Chloride solution (10% by mass) (23°C)
- ✗ Sodium Hypochlorite solution (10% by mass) (23°C)
- ✓ Sodium Carbonate solution (20% by mass) (23°C)
- ✓ Sodium Carbonate solution (2% by mass) (23°C)
- ✗ Zinc Chloride solution (50% by mass) (23°C)

Other

- ✓ Ethyl Acetate (23°C)
- ✗ Hydrogen peroxide (23°C)
- ✓ DOT No. 4 Brake fluid (130°C)
- ✓ Ethylene Glycol (50% by mass) in water (108°C)
- ✓ 1% nonylphenoxy-polyethyleneoxy ethanol in water (23°C)
- ✓ 50% Oleic acid + 50% Olive Oil (23°C)
- ✓ Water (23°C)
- ✗ Water (90°C)
- ✗ Phenol solution (5% by mass) (23°C)

Symbols used:

✓ possibly resistant

Defined as: Supplier has sufficient indication that contact with chemical can be potentially accepted under the intended use conditions and expected service life. Criteria for assessment have to be indicated (e.g. surface aspect, volume change, property change).

✗ not recommended - see explanation

Defined as: Not recommended for general use. However, short-term exposure under certain restricted conditions could be acceptable (e.g. fast cleaning with thorough rinsing, spills, wiping, vapor exposure).

Contact DuPont for Material Safety Data Sheet, general guides and/or additional information about ventilation, handling, purging, drying, etc. ISO Mechanical properties measured at 160 mil (Hytrel® measured at 80 mil), IEC Electrical properties measured at 80 mil, all ASTM properties measured at 120 mil, and test temperatures are 73°F unless otherwise stated.

The information set forth herein is furnished free of charge and is based on technical data that DuPont believes to be reliable and falls within the normal range of properties. It is intended for use by persons having technical skill, at their own discretion and risk. This data should not be used to establish specification limits nor used alone as the basis of design. Handling precaution information is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use and disposal are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. As with any product, evaluation under end-use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate or a recommendation to infringe on patents. Caution: Do not use in medical applications involving permanent implantation in the human body. For other medical applications, discuss with your DuPont customer representative and read Medical Caution H-50103-5.

Copyright © 2017 DuPont or its affiliates. All Rights Reserved. The DuPont Oval Logo, DuPont™, The miracles of science™ and all products denoted with ® or ™ are registered trademarks or trademarks of E.I. du Pont de Nemours and Company or its affiliates.

Revised: 2016-10-03

Page: 10 of 10

To find out more, visit [DuPont Performance Polymers](#) or contact nearest DuPont location.

North America

Tel: +1 302 999-4592

Toll-Free (USA): 800 441-0575

Asia Pacific

Tel: +81 3 5521 8600

Europe/Middle East/Africa

Tel: +41 22 717 51 11



Copyright 2017 DuPont. The DuPont Oval Logo is a trademark or registered trademark of E.I. du Pont de Nemours and Company or its affiliates. All rights reserved.